

DV16

Genel Özellikler / General Specifications

Ölçü / Dimensions: 2" x 1" to 4" x 2" / DN50 x DN25 to DN100 x DN50

Anma Basıncı / Nominal Pressure: 300 psi (20,6 bar)

Standartlar / Standards

Sertifikalar / Certificate: UL, FM



Bir tarafı yivli, diğer tarafı dişli olan redüksiyon, yivli sistemler ile dişli bağlantılı hat veya ekipmanlar arasında geçiş sağlar. Farklı bağlantı tiplerini birleştirerek montaj kolaylığı ve uyumluluk sunar. Küçük çaplı hat çıkışları, test noktaları ve ekipman bağlantılarında kullanılır.

The grooved x threaded concentric reducer provides a transition between grooved piping systems and threaded connections. It combines different connection types to ensure compatibility and ease of installation. Commonly used for small branch outlets, test points, and equipment connections.




Malzeme Özellikleri Material Specifications

No Parça Adı/Part Name

- Gövde/Body
- Gövde Kaplama/Body Coating

Malzeme/Material

- EN-GJS-450-10 Sfero Döküm / Ductile Iron
Fırınlanmış Epoksi Kaplama / Fusion Bonded Epoxy Coated



Boyut ve Ağırlık Tablosu Size and Weight Table

Boyut / Size			DV 16	
Ana Hat Borusu / Run Pipe			Dişli Redüksiyon / Threaded Concentric Reducer	
X			L	
mm			mm	
İnç			İnç	
60.3 2	X	33.7 1	64	2.50
		42.4 1 1/4	64	2.50
		48.3 1 1/2	64	2.50
		60.3 2	64	2.50
76.1 2 1/2	X	42.4 1 1/4	64	2.50
		48.3 1 1/2	64	2.50
		60.3 2	64	2.50
		76.1 2 1/2	64	2.50
88.9 3	X	33.7 1	64	2.50
		42.4 1 1/4	64	2.50
		48.3 1 1/2	64	2.50
		60.3 2	64	2.50
114.3 4	X	33.7 1	76	3.00
		42.4 1 1/4	76	3.00
		48.3 1 1/2	76	3.00
		60.3 2	76	3.00